








# SPRING PIZZA

# 800

|                | Modello<br><i>Model</i>   | Codice<br><i>Code</i> | Descrizione<br><i>Description</i>   |
|----------------|---|-----------------------|---|
| R404a (250 gr) |  PIZZASP820I | 7SP82IP4KA001         | 2 porte<br>2 chilled doors  |
|                | VRS1450V  | 7VS14G3D4AA01         | Vetrina refrigerata (GN1/3) + struttura vetro<br>Pans coolers (GN1/3) + glass structure |
|                | PIZZASP820I + VRS1450V  |                       |   |
| R404a (250 gr) |  PIZZASP821I | 7SP83IP4KA002         | 2 porte + 6 cassetti neutri<br>2 chilled doors + 6 ambient drawers                      |
|                | VRS2005V  | 7VS20G3D4AA01         | Vetrina refrigerata (GN1/3) + struttura vetro<br>Pans coolers (GN1/3) + glass structure |
|                | PIZZASP821I + VRS2005V  |                       |   |
| R404a (250 gr) |  PIZZASP830I | 7SP83IP4KA001         | 3 porte<br>3 chilled doors  |
|                | VRS2005V  | 7VS20G3D4AA01         | Vetrina refrigerata (GN1/3) + struttura vetro<br>Pans coolers (GN1/3) + glass structure |
|                | PIZZASP830I + VRS2005V  |                       |   |
| R404a (250 gr) |  PIZZASP831I | 7SP84IP4KA002         | 3 porte + 6 cassetti neutri<br>3 chilled doors + 6 ambient drawers                      |
|                | VRS2560V  | 7VS25G3D4AA01         | Vetrina refrigerata (GN1/3) + struttura vetro<br>Pans coolers (GN1/3) + glass structure |
|                | PIZZASP831I + VRS2560V  |                       |   |
| R404a (250 gr) |  PIZZASP840I | 7SP84IP4KA001         | 4 porte<br>4 chilled doors  |
|                | VRS2560V  | 7VS25G3D4AA01         | Vetrina refrigerata (GN1/3) + struttura vetro<br>Pans coolers (GN1/3) + glass structure |
|                | PRK840I + VRS2560V  |                       |   |
|                |   | 74768466-68           | Coppia guide a "L" per vassoi EN 600x400  |
|                |   | 74768122              | Griglia plastificata EN 600x400   |
|                |   | 74768120              | Griglia inox EN 600x400   |
|                | KIT 4 RUOTE   |                       | Sovrapprezzo per 4 ruote  |
|                | KIT 6 RUOTE   |                       | Sovrapprezzo per 6 ruote  |
|                | VERS220-60  |                       | Sovrapprezzo per Versione 220V/60Hz   |

PER ALTRI OPTIONAL E ACCESSORI VEDI PG. 164/165

\*\*\*\* Watt TN (-10/+45°C)

I gas fluorurati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.



## Tavoli Pizzeria EURONORM (EN400X600) profondità 800 mm con gruppo incorporato, in acciaio inox AISI 304.

- Isolamento 60 mm
- Piano da lavoro in granito
- Refrigerazione ventilata TN (-2/+7°C), gas refrigerante R404a (GWP3780)
- Controller elettronico con display digitale. Funzioni di overcooling e controllo umidità standard
- Accessori interni di serie per porta: 1 griglia EN400x600 plastificata su coppia guide in acciaio
- Fermo porta a 90° e richiamo automatico
- Sbrinamento a sosta ed evaporazione dell'acqua di condensa automatici
- Interni arrotondati, evaporatore rialzato e scarico integrato per una pulizia facilitata

### Optional:

filtro removibile, ozonizzatore

## S/s AISI 304 Pizza Prep Euronorm (EN400X600) counters; 800 mm depth with built-in unit.

- Insulation 60 mm
- Granite worktop
- Ventilated cooling system TN (-2/+7°C), refrigerant gas R404a (GWP3780)
- Electronic controller with digital temperature display. Overcooling and humidity control standard functions
- Standard fitting per door: 1 EN400x600 plastic coated shelf on s/s runners
- 90° stop self-closing door
- Automatic defrosting by compressor stop and automatic condensation water evaporation system
- Inner bottom panel with rounded corners, raised evaporator and integrated water discharge pipe for easy cleaning

### Optional:


removable filter, ozonizer



74768466-68



74768120



74768122



KIT 4 RUOTE



VERS220V/60HZ



| Range °C<br>Range °C | Dimensioni (mm)<br>Dimensions (mm) | Assorbimento / Absorbed power |        | Vtaggio / Voltage<br>V/Hz | Dimensioni imballo (mm)<br>Packing dimensions (mm) | Peso Netto/Lordo (Kg)<br>Net/Gross weight (kg) | Tempi di consegna<br>Delivery time   |
|----------------------|------------------------------------|-------------------------------|--------|---------------------------|--|--|--|
|                      |                                    | Watt****                      | Ampere |                           |  |  |  |
| -2/+7°C              | 1450x800x1040                      | 275                           | 5.22   | 230/50                    | 1510x860x1120                                      | 260/280  |  |
| +2/+7°C              | 1450x395x429                       | 275                           | 5.22   | 230/50                    | 1560x460x580                                       | 43/55  |  |
| -2/+7°C              | 2005x800x1040                      | 275                           | 5.22   | 230/50                    | 2064x860x1120                                      | 315/340  |  |
| +2/+7°C              | 2005x395x429                       | 275                           | 5.22   | 230/50                    | 2075x460x580                                       | 47/61  |  |
| -2/+7°C              | 2005x800x1040                      | 275                           | 5.22   | 230/50                    | 2064x860x1120                                      | 325/350  |  |
| +2/+7°C              | 2005x395x429                       | 275                           | 5.22   | 230/50                    | 2075x460x580                                       | 47/61  |  |
| -2/+7°C              | 2560x800x1040                      | 275                           | 5.22   | 230/50                    | 2620x860x1120                                      | 375/400  | Disponibile non prima di 4 settimane<br>Available not earlier than 4 weeks |
| +2/+7°C              | 2560x395x429                       | 275                           | 5.22   | 230/50                    | 2630x460x580                                       | 49/63  |  |
| -2/+7°C              | 2560x800x1040                      | 275                           | 5.22   | 230/50                    | 2620x860x1120                                      | 385/410  |  |
| +2/+7°C              | 2560x395x429                       | 275                           | 5.22   | 230/50                    | 2630x460x580                                       | 49/63  |  |

"L" pair of runners for EN 60x40 trays

Plastic coated EN 60x40 shelf

S/S EN 600x400 shelf

Price increase for 4 castors

Price increase for 6 castors

Price Increase for Power supply 220V/60Hz

FOR OTHER OPTIONS & ACCESSORIES PLEASE SEE PP. 164/165

\*\*\*\* Watt TN (-10/+45°C)

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.